Printing date: 01.01.2016 Version: 3 Revision: 01.01.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: SCARPER!

· Article number: 17-33280-2006

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

· Process category

PROC11 Non industrial spraying PROC7 Industrial spraying

· Application of the substance / the mixture Hulpmiddel

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Pesttrappa Whittington Way Chesterfield, S41 9AG Tel: 01246 264635

Tel: 01246 264635 Fax: 01246 269634

E-mail: sales@pesttrappa.com

- · Further information obtainable from: sales@pesttrappa.com
- 1.4 Emergency telephone number: During normal opening hours: Tel: 01246 269634

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS05

CHCO

· Signal word Danger

(Contd. on page 2)

Printing date: 01.01.2016 Version: 3 Revision: 01.01.2016

Trade name: SCARPER!

(Contd. of page 1)

· Hazard-determining components of labelling:

Alkyl Polyglycol Ether Oil of Hartshorn propan-2-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves / eye protection.
P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Active substance with propellant

· Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	dimethyl ether Flam. Gas 1, H220; Press. Gas C, H280	25-<50%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%
CAS: 8001-85-2 EINECS: 232-294-3	Oil of Hartshorn Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 4, H413	10-<25%
	Alkyl Polyglycol Ether Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302	2.5-<10%
	MORPHOLINE 43-00000-3024 Flam. Liq. 3, H226; Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	0.1-<1%

· Additional information:

- Gl

Printing date: 01.01.2016 Version: 3 Revision: 01.01.2016

Trade name: SCARPER!

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

 \cdot 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

Printing date: 01.01.2016 Version: 3 Revision: 01.01.2016

Trade name: SCARPER!

(Contd. of page 3)

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

MORPHOLINE 43-00000-3024

WEL Short-term value: 72 mg/m³, 20 ppm Long-term value: 36 mg/m³, 10 ppm Sk

· DNELs

67-63-0 propan-2-ol

0. 00 0 P	·· ·· · · · · · · · · · · · · · · · ·			
Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)		
Dermal	DNEL Long term-systemic	319 mg/kg bw/day (Consumer)		
		888 mg/kg bw/day (Worker)		
Inhalative	DNEL Long term-systemic	89 mg/m3 (Consumer)		
		500 mg/m3 (Worker)		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

(Contd. on page 5)

Printing date: 01.01.2016 Version: 3 Revision: 01.01.2016

Trade name: SCARPER!

· Protection of hands:

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Solvent resistant gloves

Wear gloves for the protection against chemicals according to EN 374

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.5 \text{ mm}$

· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

· Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

· 9.1	Information	on	basic p	ohysical	and	chemical	l properties
-------	-------------	----	---------	----------	-----	----------	--------------

· General Information

· Appearance:

· pH-value:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· Change in condition

Melting point/Melting range:

Boiling point/Boiling range:

-24 °C

· Flash point: -42 °C

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 235 °C

• **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

• **Danger of explosion:** Product is not explosive. However, formation of explosive air/

Not determined.

vapour mixtures are possible.

(Contd. on page 6)

Printing date: 01.01.2016 Version: 3 Revision: 01.01.2016

Trade name: SCARPER!

		(Contd. of page
· Explosion limits:		
Lower:	2.0 Vol %	
Upper:	18.6 Vol %	
· Vapour pressure at 20 °C:	5200 hPa	
· Density at 20 °C:	0.88 g/cm ³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	vater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	45.6 %	
Water:	39.2 %	
Solids content:	0.1 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

· LD/LC50	· LD/LC50 values relevant for classification:				
67-63-0 pi	67-63-0 propan-2-ol				
Oral		5840 mg/kg (rat)			
Dermal	LD50	50 13900 mg/kg (rabbit)			
Inhalative	LC50/6h	25000 mg/m3 (rat)			
Alkyl Poly	Alkyl Polyglycol Ether				
Oral	LD50	200-2000 mg/kg (rat)			
Duimony	Drimony invitant offset				

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date: 01.01.2016 Version: 3 Revision: 01.01.2016

Trade name: SCARPER!

(Contd. of page 6)

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

•	Aq	uat	tic	toxicity	:
			^		_

67-63-0 propan-2-ol

LC50 (24h) 9714 mg/l (Daphnia magna) LC50/96h 9640 mg/l (Pimephales promelas) LOEC (8 days) 1000 mg/l (algae)

Alkyl Polyglycol Ether

LC50/96h 0.1-1 mg/l (Fish)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

•	14.	1 U	JN.	·Nu	mb	er
---	-----	-----	-----	-----	----	----

· ADR, ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR, ADN UN1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

(Contd. on page 8)

Printing date: 01.01.2016 Version: 3 Revision: 01.01.2016

Trade name: SCARPER!

(Contd. of page 7) · 14.3 Transport hazard class(es) $\cdot \, ADR$ 2 5F Gases. · Class · Label 2.1 \cdot ADN 2 5F · ADN/R Class: · IMDG, IATA · Class 2.1 · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Danger code (Kemler): · EMS Number: F-D,S-U · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · Limited quantities (LQ) Code: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category · Tunnel restriction code D · IMDG · Limited quantities (LQ) 1L Code: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity · UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 9)

Printing date: 01.01.2016 Version: 3 Revision: 01.01.2016

Trade name: SCARPER!

(Contd. of page 8)

- · National regulations:
- · Technical instructions (air):

Class	Share in %
Wasser	25-<50
NK	25-<50

- · VOC-CH 45.00 %
- · VOC-EU 612.6 g/l
- · Danish MAL Code 5-3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H413 May cause long lasting harmful effects to aquatic life.

- · Department issuing MSDS: Research & Development
- · Contact: Ing. J. Sleumer
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

(Contd. on page 10)

Page 10/10

Safety data sheet According to 1907/2006 EEC Article 31

Printing date: 01.01.2016 Version: 3 Revision: 01.01.2016

Trade name: SCARPER!

(Contd. of page 9)

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1
Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4

* Data compared to the previous version altered. *